

# Package: PVR (via r-universe)

August 26, 2024

**Type** Package

**Title** Phylogenetic Eigenvectors Regression and Phylogentic  
Signal-Representation Curve

**Version** 0.3

**Date** 2018-05-29

**Author** Thiago Santos

**Maintainer** Thiago Santos <thiago.santos@ufvjm.edu.br>

**Description** Estimates (and controls for) phylogenetic signal through  
phylogenetic eigenvectors regression (PVR) and phylogenetic  
signal-representation (PSR) curve, along with some plot  
utilities.

**License** GPL (>= 2)

**Imports** splancs, ape, methods, graphics, stats, utils, MASS

**NeedsCompilation** no

**Date/Publication** 2018-05-30 22:29:01 UTC

**Repository** <https://santostbio.r-universe.dev>

**RemoteUrl** <https://github.com/cran/PVR>

**RemoteRef** HEAD

**RemoteSha** 2c00e7db9ed26c1e7fc106ad77cc12dd9b238463

## Contents

PVR-package . . . . .	2
PSR . . . . .	3
PSR-class . . . . .	4
PSRplot . . . . .	6
PVR . . . . .	7
PVR-class . . . . .	9
PVRdecomp . . . . .	10
VarPartplot . . . . .	11

<b>Index</b>	<b>13</b>
--------------	-----------

---

PVR-package

*Computes Phylogenetic eigenVectors Regression and Phylogenetic Signal-Representation curve (with null and neutral expectations).*

---

## Description

Computes PVR and PSR curve along with some plot utilities.

## Details

Package: PVR  
Type: Package  
Version: 1.0  
Date: 2018-05-29  
License: GPL >= 2

## Author(s)

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

Maintainer: Thiago Santos <thiago.santos@ufvjm.edu.br>

## References

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interspecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

## See Also

[PVR-class](#), [PSR-class](#), [PVR](#), [PSR](#), [PVRdecomp](#), [PSRplot](#), [VarPartplot](#)

## Examples

```
library(splancs)
#Creating a 10 tips ultrametric random phylogeny
library(ape)
tree <- rcoal(10)
#Decomposing phylogenetic distance matrix derived from tree into a set of orthogonal vectors
```

```
x <- PVRdecomp(tree)
trait <- runif(10)
y <- PSR(x, trait)
y
```

---

PSR

*Creates a phylogenetic signal-representation (PSR) curve for a given phylogeny and trait set and computes its area.*

---

### Description

Phylogenetic signal-representation (PSR) curve, built upon phylogenetic eigenvector regression (PVR). Sequential PVR models are fitted after successively increasing the number of eigenvectors and plotting their R<sup>2</sup> against the accumulated eigenvalues. The PSR area, expressing deviations from Brownian motion, is strongly correlated with Blomberg's K-statistics, so nonlinear PSR curves reveal if traits are evolving at a slower or higher rate than expected. The PSR area is also correlated with phylogenetic half-life under an OU process, so both methods describe the relationship between interspecific variation and time since divergence among species shape.

### Usage

```
PSR(x, trait = NULL, null.model = FALSE, Brownian.model = FALSE, times = 1000)
```

### Arguments

<code>x</code>	A object of class PVR (created using PVRdecomp function).
<code>trait</code>	A vector, data frame or matrix that contains continuous or binary traits sets (for data frames and matrices, each column must represent a trait set). For now, only the first column will be used.
<code>null.model</code>	Logical. Should the function estimates the null expectation for the PSR area. Default is FALSE.
<code>Brownian.model</code>	Logical. Should the function estimates the Brownian (neutral) expectation for the PSR area. Default is FALSE.
<code>times</code>	Number of iterations used in null.model and Brownian.model.

### Value

PSR function returns a object of (S4) class PSR that extends the (S4) class PVR, by adding: a PSR slot that contains the area (and p if null.model = TRUE) for each trait set, the cumulative eigenvalues and R<sup>2</sup> that determine the curve; a slot with the null and neutral expectations (if any).

### Author(s)

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

## References

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interespecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

## See Also

[PVR](#), [PVRdecomp](#), [PSRplot](#), [VarPartplot](#)

## Examples

```
library(splancs)
#Creating a 10 tips ultrametric random phylogeny
library(ape)
tree <- rcoal(10)
#Decomposing phylogenetic distance matrix derived from tree into a set of orthogonal vectors
x <- PVRdecomp(tree)
trait <- runif(10)
y <- PSR(x, trait)
summary(y)
```

---

PSR-class

*Class "PSR"*

---

## Description

A S4 class that extends S4 PVR class in order to accommodate PSR analysis results.

## Objects from the Class

Objects can be created by calls of the form `new("PSR", ...)`.

## Slots

`PSRarea`: Object of class `"data.frame"` that contains PSR curve area.

`PSR`: Object of class `"data.frame"` that contains accumulated r squared and eigenvalues.

`Expect.area.values`: Object of class `"list"` that contains the expected null and neutral area values.

`nullPSR`: Object of class `"matrix"` nested in the `Expect.area.values` slot that contains the expected null area values.

**BrownianPSR:** Object of class "matrix" nested in the Expect.area.values slot that contains the expected Brownian (neutral) area values.

**Eigen:** Object of class "list" that contains the eigenvalues and eigenvectors generated by phylogenetic distance matrix eigendecomposition. Inherited from PVR class.

**phyDist:** Object of class "matrix" that contains a phylogenetic distance matrix. Inherited from PVR class.

**phylo:** Object of class "phylo" that contains a phylogeny. Inherited from PVR class.

**Selection:** Object of class "list" that contains the selection method (along with its statistics) used to select the vectors, the selected vectors IDs and a matrix that contains the selected vectors. Inherited from PVR class.

**PVR:** Object of class "list" that contains the **Phylogenetic EigenVectors Regression r squared** and residuals. Inherited from PVR class.

**VarPart:** Object of class "list" that contains the variation partition components. Inherited from PVR class.

### Extends

Class "PVR", directly.

### Methods

**plot** signature(x = "PSR"): ...  
**show** signature(object = "PSR"): ...

### Author(s)

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

### References

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.

Legendre, P. and Legendre, L. (1998). *Numerical ecology*, 2nd Englished. Elsevier.

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interspecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

### See Also

[PVR-class](#), [PVR](#), [PSR](#), [PVRdecomp](#), [PSRplot](#), [VarPartplot](#)

### Examples

```
showClass("PSR")
```

---

PSRplot

*Plot function for objects of class PSR*

---

### Description

Plot PSR curve along with null and neutral expectations curves.

### Usage

```
PSRplot(x, info = c("area", "null", "Brownian", "both"), ...)
```

### Arguments

x	An object of class PSR
info	Type of information to be plotted. It can be "area" (to plot only the PSR curve), "null" (to plot PSR curve and null PSR curve), "neutral" (to plot PSR curve and neutral PSR curve) and "both" (to plot PSR curve and both null and neutral PSR curve).
...	Parameters passed to the plot function.

### Author(s)

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

### References

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interspecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

### See Also

[PSR](#), [PVRdecomp](#), [PVR](#), [VarPartplot](#)

### Examples

```
library(splancs)
#Creating a 10 tips ultrametric random phylogeny
library(ape)
tree <- rcoal(10)
#Decomposing phylogenetic distance matrix derived from tree into a set of orthogonal vectors
x <- PVRdecomp(tree)
```

```

trait <- runif(10)
res <- PSR(x, trait = trait, null.model = TRUE, Brownian.model = TRUE, times = 10)
PSRplot(res, info = "both")

```

PVR

*Phylogenetic eigenvectors regression.***Description**

The phylogenetic eigenvector regression (PVR) starts by performing an eigendecomposition of a pairwise double-centered phylogenetic distance matrix between species. The eigenvectors (representing the traits under analysis) estimated values express phylogenetic trends in data and residuals express independent evolution of each species.

**Usage**

```

PVR(x, phy, trait, envVar, method="moran", weights,
scaled=FALSE, sig=TRUE, sig.t=0.05, MI.t=0.05, psr.t=0.01,
accvalue.t=0.9, ...)

```

**Arguments**

x	An object of class PVR (created by the PVRdecomp function) or class PSR (required by the "PSR" method).
phy	An object of class phylo that contains an ultrametric phylogeny.
trait	A vector, data frame or matrix that contains traits sets (for data frames and matrices, each column must represent a trait set).
envVar	A vector, data frame or matrix that contains environmental variables. Used to estimates the variation of a trait set that is explained by phylogeny and by environment.
method	Character string. A name for the eigenvectors selection method. It can be "moran", "stepwise", "psr" or "sequential".
weights	Weighting matrix based on Phylogenetic distances used in the "moran" method. If no weights matrix is provided, weights will be set to $\max(D) - D_{ij}$ , where D is the phylogenetic distance matrix.
scaled	Logical. Should the phylogenetic distances be scaled into the range of 0 to 1. Default is FALSE.
sig	Logical. Should the eigenvectors selected by the "moran" method be selected by the significance of residuals autocorrelation. If FALSE the eigenvectors will be selected by Moran's I values.
MI.t	Minimum residuals Moran's I value used to select eigenvectors when significance is FALSE.
sig.t	The significance threshold used to select eigenvectors by the "moran" method.
psr.t	The minimum acumulate R2 gain threshold used to select eigenvectors by the "PSR" method.

accvalue.t      Relative accumulated eigenvalue threshold use to select the eigenvectors by the "sequential" method.  
 ...              Parameters passed to the stepwise regression used in the "AIC" method

**Value**

A PVR class object.

**Author(s)**

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

**References**

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution*, 52:1247-1262.

Legendre, P. and Legendre, L. (1998). *Numerical ecology*, 2nd Englished. Elsevier.

Desdevises, Y., Legendre, P., Azouzi, L. and Morand, S. (2003). Quantifying phylogenetic structured environmental variation, *Evolution*, 57(11):2647-2652

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interespecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

**See Also**

[PSR](#), [PVRdecomp](#), [PSRplot](#), [VarPartplot](#)

**Examples**

```
library(ape)
tree <- rcoal(10)
#Decomposing phylogenetic distance matrix derived from tree into a set of orthogonal vectors
x <- PVRdecomp(tree)
trait <- runif(10)
y <- PVR(x, trait = trait, method = "morán")
str(y)
```



PVR-class

Class "PVR"

**Description**

A S4 class that contains eigenvalues and eigenvectors from decomposition of a phylogenetic distance matrix and PVR r squared and residuals.

**Objects from the Class**

Objects can be created by calls of the form `new("PVR", ...)`.

**Slots**

**Eigen:** Object of class "list" that contains the eigenvalues and eigenvectors generated by phylogenetic distance matrix eigendecomposition.

**phyDist:** Object of class "matrix" that contains a phylogenetic distance matrix.

**phylo:** Object of class "phylo" that contains a phylogeny.

**Selection:** Object of class "list" that contains the selection method (along with its statistics) used to select the vectors, the selected vectors IDs and a matrix that contains the selected vectors.

**PVR:** Object of class "list" that contains the **Phylogenetic EigenVectors Regression r squared** and residuals.

**VarPart:** Object of class "list" that contains the variation partition components.

**Methods**

**show** signature(object = "PVR"): Always print the Eigen slot.

**Author(s)**

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

**References**

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.

Legendre, P. and Legendre, L. (1998). *Numerical ecology*, 2nd Englished. Elsevier.

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interspecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

**See Also**

[PSR-class](#), [PVR](#), [PSR](#), [PVRdecomp](#), [PSRplot](#), [VarPartplot](#)

**Examples**

```
showClass("PVR")
```

---

PVRdecomp

*Phylogenetic distances matrix (eigen)decomposition.*

---

**Description**

The PVRdecomp function decompose phylogenetic distance matrices (computed based on phylogenies) into a set of orthogonal eigenvectors

**Usage**

```
PVRdecomp(phy, type = "newick", dist = NULL, scale = FALSE, ...)
```

**Arguments**

phy	An object of class phylo that contains a ultrametric phylogeny with branch lengths or a character string that represents a phylogeny file (must have full path) of type given by type.
type	A character string with the phylogeny file format. It can be "newick" or "nexus". Used only if phy is a character string, ignored otherwise.
dist	A phylogenetic distance matrix. Not used.
scale	Logical. Should the phylogenetic distances be scaled into the range of 0 to 1. Default is FALSE.
...	Not used.

**Value**

The PVRdecomp function returns a object of (S4) class PVR with an Eigen slot that contains eigenvalues and eigenvectors computed after the matrix decomposition.

**Author(s)**

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

## References

Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.

Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interespecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.

Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

## See Also

[PVR](#), [PSR](#)

## Examples

```
library(ape)
tree <- rcoal(10)
#Decomposing phylogenetic distance matrix derived from tree into a set of orthogonal vectors
x <- PVRdecomp(tree, scale = TRUE)
str(x)
```

---

VarPartplot	<i>Plot function for objects of class PVR to show variation partition components.</i>
-------------	---

---

## Description

Plot a, b, c and d components of traits variation partition between phylogeny and environment (as defined by Desdevises et al., 2003).

## Usage

```
VarPartplot(x, ...)
```

## Arguments

x	An object of class PVR with a non NULL slot VarPart.
...	Parameters passed to the plot function.

## Author(s)

Santos, T; Diniz-Filho, J.A.F.; Rangel, T.F.; Bini, L.M.

## References

- Diniz-Filho, J.A.F., Sant'Ana, C.E.R. and Bini, L.M. (1998). An eigenvector method for estimating phylogenetic inertia. *Evolution* 52:1247-1262.
- Legendre, P. and Legendre, L. (1998). *Numerical ecology*, 2nd Englished. Elsevier.
- Desdevises, Y., Legendre, P., Azouzi, L. and Morand, S. (2003). Quantifying phylogenetic structured environmental variation, *Evolution*, 57(11):2647-2652.
- Diniz-filho, J.A.F., Rangel, T.F., Santos, T. and Bini, L.M. (2012). Exploring patterns of interspecific variation in quantitative traits using sequential phylogenetic eigenvector regressions. *Evolution*, 66(4):1079-1090.
- Diniz-filho, J.A.F., Bini, L.M., Rangel, T.F., Morales-Castilla, I., Olalla-Tarraga, M.A., Rodriguez, M.A. and Hawkins, B.A. (2012). On the selection of phylogenetic eigenvectors for ecological analyses. *Ecography*, 35:239-249.

## See Also

[PSR](#), [PVRdecomp](#), [PVR](#), [PSRplot](#)

## Examples

```
library(ape)
tree <- rcoal(10)
#Decomposing phylogenetic distance matrix derived from tree into a set of orthogonal vectors
x <- PVRdecomp(tree)
trait <- runif(10)
envvar <- runif(10)
y <- PVR(x, trait = trait, envVar = envvar, method = "moran")
VarPartplot(y)
```

# Index

- \* **PSR area**
    - PSRplot, [6](#)
  - \* **PSR**
    - VarPartplot, [11](#)
  - \* **PVR**
    - PSRplot, [6](#)
  - \* **Phylogenetic models**
    - PVR, [7](#)
  - \* **Phylogenetic signal**
    - PVR, [7](#)
    - VarPartplot, [11](#)
  - \* **classes**
    - PSR-class, [4](#)
    - PVR-class, [9](#)
  - \* **package**
    - PVR-package, [2](#)
  - \* **phylogenetic signal**
    - PSR, [3](#)
    - PVRdecomp, [10](#)
  - \* **phylogeny**
    - PSR, [3](#)
    - PVRdecomp, [10](#)
- plot, PSR-method (PSR-class), [4](#)  
PSR, [2](#), [3](#), [5](#), [6](#), [8](#), [10–12](#)  
PSR-class, [4](#)  
PSRplot, [2](#), [4](#), [5](#), [6](#), [8](#), [10](#), [12](#)  
PVR, [2](#), [4–6](#), [7](#), [10–12](#)  
PVR-class, [9](#)  
PVR-package, [2](#)  
PVRdecomp, [2](#), [4–6](#), [8](#), [10](#), [10](#), [12](#)
- show, PSR-method (PSR-class), [4](#)  
show, PVR-method (PVR-class), [9](#)
- VarPartplot, [2](#), [4–6](#), [8](#), [10](#), [11](#)